



EV STATIONN

📍 8004 Winbrook Dr, Benbrook TX 76126

@ support@evstationn.com

☎ +1 650 444 1214

EVSTN CP5

Level 2

Up to 2*80A



ONE CHARGER, TWO OUTPUT



POWERFUL

Up to 80A / 19.2kW of charging capacity



FLEXIBLE

Cable management allows access from either side of the vehicle.



INTERACTION

7" touch screen for easy use



CONNECTED

Complete with LAN connectivity (Wi-Fi or 4G optional), ensuring chargers are always online.



OCPP

OCPP 1.6J help you connect EV charger to the cloud.



DURABILITY

IP65 and IK08 protection ratings, allowing for indoors or outdoors



DATASHEET

Model No	JNT-EVSTNP5
Input Voltage	208-240 Vac
Frquency	50-60Hz
Amperage	80A+80A
Max. Power Output	119.2kW+19.2kW
Net Weight	177.5lbs
Gross Weight	165 lbs
Product Dimensions	2073"x 577"x 284"
Package Dimensions (Top/Bottom Part)	727"x 661"x 283" / 1534 / 1534"x 534"x 389"

Protection & Standard

Charging Interface	SAE J1772 Compliant, Type 1 Plug
Safety Compliance	UL2594, UL2231-1/-2
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection

Environmental

Operating Temp.	-22 F to 122 F
Relative Humidity	Up to 95% non-condensing
Cable Length	18ft Standard